

## SPECIFICATIONS

# HAHN HFP160

### *Firewood Pro*

- Length: 120"
- Weight: 2020 lbs, (std config)
- Hydraulic Requirements 20gpm/2500psi
- Electrical Requirements 12 vdc (24vdc optional)
- Hydraulic connections 3--Press, Return, Case Drain
- Control Valves Solenoid Operated, mounted on the processor, electric/hydraulic; All functions operated by push buttons on side pods clamped to loader's joysticks
  
- Saw Bar Bar-18H (Harvester)
- Saw Chain .404HX (Harvester)
- Saw Motor Bent Axis, Piston Type
- Saw Oiler Automatic; Oils with bar oil
- Max Saw Cut Diameter 18"
  
- Splitter Cylinder Bore & Stroke 4" x 24"; 2-1/4" Rod
- Split Force @2500 psi Hi Power Mode: 31,400lbs  
Hi Speed Mode: 11,116lbs
- Split Speed @ 20gpm Hi Power Mode: 2.6 sec  
Hi Speed Mode: 1.75 sec
  
- Wedges Std-4 way; optional 6 & 8 Hyd. Adjustable, optional
  
- Cut Lengths 16" std; 14",18", 20, optional
  
- Infeed Roller Chain Conveyor w/ Powered Spike Roller Assist.

OTHER FEATURES: Detachable Splitter Heads, Universal Quick-Tach Mount, Replaceable Primary Wedge, Heavy Duty Construction

Specifications are subject to change without notice. Please verify actual specifications prior to purchase.