


REMU L 85

PICTURE WILL COME SHORTLY

Dimensions

- A** Width 162 cm
- B** Depth 93 cm
- C** Height 85 cm



Weight

810 kg

For excavators

6 – 8 tn

For wheel loaders

2 – 3 tn *

skid-steers and tractors

Hydr.flow recommendation

60 – 100 l/min

Volume ISO/SAE

0,5/0,8 m³

Screening area

0,8 m²

Hydr. power continous/ peak

20/28 kW

Number of axles

2

Blade thickness and material

8 mm Hardox 500

Standard blade spacings

20 mm (grain size 0-15 mm)

27 mm (grain size 0-22 mm)

34,5 mm (grain size 0-30 mm)

48 mm (grain size 0-43 mm)

Working pressure 120 – 160 bar, max. pressure 210 bar.

* Please note when used with combination machines where back and front attachments are possible the recommended base machine weights can be higher

Main applications: topsoil screening, producing quality soil and mixed materials, pipe back filling, screening demolition worksite waste materials, wood chip screening (and crushing) recycling materials, composting, aerating biomaterials, screening stones, soil, glass, metals, peat, bark, clay, bio waste, demolition waste

- Remu L85 screening bucket is lightweight and compact in tight places like greenhouses and gardens
- The unique blade design eliminates clogging and makes the best result even in wet conditions when other methods have to stop.
- An universal tool for landscaping, fits in most front- and backyards
- Remu range includes buckets for 5-30 ton excavators, 2-20 ton wheel loaders, skid-steer/ loaders and tractors